

Merker Dryer topLine pro TA 9340, TC9350, TW9360



topLine pro TA9340

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Exhaust air system
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish



topLine pro TC9350

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Condensation system
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish



topLine pro TW9360

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Condensation system with heat pump
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish

Dryer topLine pro

Company or brand name	Merker		Merker	Merker
Type of appliance	Exhaust air dryer		Condensation dryer with heat-exchanger air	Condensation dryer with heat pump
Type or sales description	topLine pro TA 9340		topLine pro TC 9350	topLine pro TW 9360
Product number	9340.1U		9350.1U	9360.1U
Load capacity	max. kg	8	8	8
Structural design				
Stand-alone unit with work surface	•		•	•
Standard unit for washing and drying tower	•		•	•
Door hinge ³⁾	r/l/w		r/l/w	r/l/w
Dimensions ⁴⁾				
Height	cm	90	90	90
Width	cm	63	63	63
Depth including distance from wall	cm	83	84	84
Height for built-in installation	cm	90,5	90,5	90,5
Depth with door open	cm	144	146	146
Height (adjustable)	cm	2	2	2
Drying control				
By time selection ⁵⁾	•		•	•
Automatic by electronic moisture detection ⁶⁾	•		•	•
System and Equipment				
Drying technology	Air extraction system		Air condensation system	Condensation system with heat pump
Programme time display	•		•	•
Automatic door opening	•		•	•
Loading opening	cm	front, ☒ 36 / 31 / 180°	front, ☒ 36 / 31 / 180°	front, ☒ 36 / 31 / 180°
LED drum lighting	•		•	•
Connecting cable	m	1,5	1,5	1,5
Outlet hose	m	–	2 / ☒ 22 mm	2 / ☒ 22 mm
Condensate drainage in container / Drainage direct	–		•	•
Exhaust air duct	☒ 100 mm, 90°-angle adapter		–	–
Maximum drain height	m	–	1	1
Exhaust hose ☒ 100 mm	m	2	–	–
Power supply – Electrical connection ⁷⁾				
Voltage	V	400 V 3N~/400 V 2N~/230 V 1N~	400 V 3N~/400 V 2N~/230 V 1N~	400 V 2N~
Connected values	kW	5,9 / 4,4 / 2,2	5,1 / 3,7 / 2,3	3,4
Fuse protection	AT	10/10/10	10/10/10	10
Safety and service				
Conforms to the European Machinery Directive	2006/42/EC		2006/42/EC	2006/42/EC
Country of origin	Switzerland		Switzerland	Switzerland
Guarantee ⁸⁾	1 year		1 year	1 year
Service by	Merker Maschinen AG			
Name and address of supplier	Merker Maschinen AG, CH-8633 Wolfhausen/ZH			

Explanations:

- Available or yes • Not available or no
- 3) Door hinge: l= left, r= right, w= can be changed
Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.
- 4) The stated dimensions are minimum dimensions for the niche where the machine is built in.
Further dimensions can be found in the dimension sheets.
- 5) Set the degree of drying according to the laundry items, as shown in the operating instructions.
- 6) Degree of drying is maintained automatically.
- 7) Information on switchover options can be found in the installation instructions, where required.