

PROFESSIONAL WASHER EXTRACTOR PROFESSIONAL DRYER

6,5 KG

FEATURES WASHER EXTRACTOR

- Titanium grey cabinet
- Stainless steel drum and tub
- Easy to use timer
- Mop and medical programmes
- Soap hopper at the front
- Matching dryer available – space saving when placed on top

OPTIONS WASHER EXTRACTORS

- Drain valve
- Marine voltages available

ACCESSORIES WASHER EXTRACTORS

- External coin meter
- Liquid soap pumps

FEATURES DRYERS

- Titanium grey cabinet
- Stainless steel drum
- Large door opening (Ø 45 cm)

OPTIONS DRYERS


- Condens unit (DAMC)
- Marine voltages available
- Heat pump heating (DAM6 HP)

ACCESSORIES DRYERS

- External coin meter



COMPACT
DESIGN



STACKABLE
UNIT



ENERGY
EFFICIENT

TYPE		WASHER
CAPACITY	kg	6,5
DRUM VOLUME	l	60
DRUM DIAMETER	mm	Ø 480
EXTRACTION SPEED	rpm	1400
G-FACTOR		530
ELECTRICAL CONNECTION		With drainpump: 208-240V/60/1 380-415V/50/3Ph+N* 440V/60/3Ph-N
ELECTRICAL HEATING	kW	3,2
CIRCUIT BREAKER		230V-16A/400V-10A
WATER CONNECTION	inch	3/4"
DRAIN		Pump Standard, Drain valve available
DIMENSIONS HxWxD	mm	850x595x585
Net weight	kg	73
TRANSPORT DATA		
Volume (packed)	m ³	0,53
Packed HxWxD	mm	915x610x660
Gross weight	kg	77

TYPE		DRYER vented	DRYER condense	DRYER heat pump
CAPACITY	kg	6,5		
DRUM VOLUME	l	112		
DIMENSIONS DRUM	mm	Ø 571x476		
ELECTRICAL CONNECTION		208-240V/60/1 380-415V/50/3Ph+N 440V/60/3Ph-N	380-415V/50/3Ph+N	208-240V/50/1Ph
ELECTRICAL HEATING	kW	3	2,5	1,3
CIRCUIT BREAKER		230V-16A 400V-10A		230V-10A
AIRFLOW	m ³ /h	123	245	internal
AIR EVACUATION	mm	100	-	-
DIMENSIONS HxWxD	mm	850x595x585		
Net weight	kg	39	47	52
TRANSPORT DATA				
Volume (packed)	m ³	0,53		
Packed HxWxD	mm	915x610x660		
Gross weight	kg	45	50	56

* available with drain valve

